

## DISTRIBUTED FEEDBACK (DFB) QC LASERS

AdTech Optics DFB-QCL chips are designed and fabricated to handle CW or Pulse operation. Several mounting options available. Please contact our expert engineering staff for inquiries in pricing and availability.

Available DFB Wavelengths					
WaveNumber	Wavelength (um)	WaveNumber	Wavelength (um)	WaveNumber	Wavelength (um)
2265 - 2260	4.41 - 4.42	1940 - 1936	5.15 - 5.16	1299 - 1295	7.69 - 7.72
2250 - 2246	4.44 - 4.45	1938 - 1936	5.160 - 5.165	1290 - 1286	7.75 - 7.77
2235 - 2231	4.47 - 4.48	1928 - 1926	5.18 - 5.19	1280 - 1277	7.81 - 7.83
2225 - 2221	4.49 - 4.50	1917 - 1914	5.21 - 5.22	1277 - 1273	7.83 - 7.85
2220 - 2215	4.50 - 4.51	1696 - 1693	5.89 - 5.90	1269 - 1265	7.88 - 7.90
2210 - 2205	4.52 - 4.53	1687 - 1684	5.92 - 5.93	1111	9.00
2205 - 2200	4.53 - 4.54	1662 - 1661	6.01 - 6.02	1108	9.02
2195 - 2192	4.55 - 4.56	1661 - 1658	6.02 - 6.03	1107 - 1106	9.03 - 9.04
2190 - 2187	4.56 - 4.57	1655 - 1651	6.04 - 6.05	1104 - 1102	9.05 - 9.07
2186 - 2182	4.57 - 4.58	1417 - 1412	7.05 - 7.08	1074	9.31
2181 - 2178	4.58 - 4.59	1409 - 1405	7.09 - 7.11	1071 - 1070	9.33 - 9.34
1991 - 1988	5.02 - 5.03	1392 - 1391	7.183 - 7.189	1069 - 1067	9.35 - 9.37
1966 - 1963	5.08 - 5.09	1386 - 1382	7.21 - 7.23	1063 - 1060	9.40 - 9.43
1951 - 1948	5.12 - 5.13	1321 - 1317	7.57 - 7.59	1058 - 1055	9.45 - 9.47
1944 - 1941	5.14 - 5.15	1309 - 1303	7.63 - 7.67	1054 - 1051	9.48 - 9.51


*\*Measured at T = 15°C in Pulse Operation, Duty Cycle <1 %*

### Mounting Options:



#### C-Mount :

- Dim: 6 x 4 x 4 mm (excluding leads)



#### Laboratory Module:

- Dim: 2.2 x 2.5 x 1 in.
- Includes: Collimating Lens, TEC, Temperature and Moisture Sensor, Connectors.

Please feel free to contact us for any further clarification or details you may need.

AdTech Sales Staff  
 + 1 (626) 956-1000  
[sales@atoptics.com](mailto:sales@atoptics.com)