

DISTRIBUTED FEEDBACK (DFB) QC LASERS

AdTech Optics DFB-QCL chips are designed and fabricated to handle CW or Pulse operation. Several mounting options available. Please contact our expert engineering staff for inquiries in pricing and availability.

Available DFB Wavelengths*					
WaveNumber	Wavelength (μm)	WaveNumber	Wavelength (μm)	WaveNumber	Wavelength (μm)
2249 - 2246	4.44 - 4.45	1917 - 1914	5.21 - 5.22	1386 - 1382	7.21 - 7.23
2234 - 2230	4.47 - 4.48	1895 - 1891	5.27 - 5.28	1321 - 1317	7.57 - 7.59
2225 - 2221	4.49 - 4.50	1890 - 1886	5.29 - 5.30	1299 - 1295	7.69 - 7.72
2219 - 2214	4.50 - 4.51	1696 - 1693	5.89 - 5.90	1290 - 1286	7.75 - 7.77
2210 - 2205	4.52 - 4.53	1687 - 1684	5.92 - 5.93	1269 - 1265	7.88 - 7.90
2204 - 2200	4.53 - 4.54	1662 - 1661	6.01 - 6.02	1108	9.02
2195 - 2192	4.55 - 4.56	1661 - 1658	6.02 - 6.03	1104 - 1102	9.05 - 9.07
2192 - 2187	4.56 - 4.57	1655 - 1651	6.04 - 6.05	1074 - 1072	9.31 - 9.32
2184 - 2182	4.57 - 4.58	1638 - 1634	6.10 - 6.11	1071 - 1070	9.33 - 9.34
2181 - 2178	4.58 - 4.59	1398 - 1395	7.15 - 7.16	1059 - 1056	9.44 - 9.46
1951 - 1948	5.12 - 5.13	1394 - 1390	7.17 - 7.19	1056 - 1054	9.46 - 9.48
1940 - 1936	5.15 - 5.16	1391 - 1386	7.18 - 7.21	1053 - 1050	9.49 - 9.52
1928 - 1926	5.18 - 5.19	1387 - 1384	7.20 - 7.22		


*Measured at T = 15°C in Pulse Operation, Duty Cycle <1 %

Mounting Options:



C-Mount :

- Dim: 6 x 4 x 4 mm (excluding leads)



Laboratory Module:

- Dim: 2.2 x 2.5 x 1 in.
- Includes: Collimating Lens, TEC, Temperature and Moisture Sensor, Connectors.

Please feel free to contact us for any further clarification or details you may need.

AdTech Sales Staff
 + 1 (626) 956-1000
sales@atoptics.com